

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 8.0 Revision Date 03.06.2021 Print Date 17.10.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Collodion 4%

Product Number : 1.02644 Catalogue No. : 102644 Brand : Millipore

REACH No. : This product is a mixture. REACH Registration Number see

section 3.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Pharmaceutical production, Reagent for development and

research, Cosmetic raw material

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Chemie GmbH

Eschenstrasse 5

D-82024 TAUFKIRCHEN

Telephone : +49 (0)89 6513-1130Fax : +49 (0)89 6513-1161

E-mail address : technischerservice@merckgroup.com

1.4 Emergency telephone

Emergency Phone # : 0800 181 7059 (CHEMTREC Deutschland)

+49 (0)696 43508409 (CHEMTREC

weltweit)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 1), H224 Acute toxicity, Oral (Category 4), H302

Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram

Signal word Danger

Millipore- 1.02644 Page 1 of 13



Hazard statement(s)

H224 Extremely flammable liquid and vapor.

H302 Harmful if swallowed.

H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P301 + P312 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel

unwell.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Supplemental Hazard information (EU)

EUH019 May form explosive peroxides.

EUH066 Repeated exposure may cause skin dryness or cracking.

Reduced Labeling (<= 125 ml)

Pictogram

Signal word Danger

Hazard statement(s)

H224 Extremely flammable liquid and vapor.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Supplemental Hazard information (EU)

EUH019 May form explosive peroxides.

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Component		Classification	Concentration
Diethyl ether			
CAS-No. EC-No.	60-29-7 200-467-2	Flam. Liq. 1; Acute Tox. 4; STOT SE 3; H224, H302,	>= 70 - < 90 %
Index-No.	603-022-00-4	H336	70
Registration number	01-2119535785-29- XXXX	Concentration limits: >= 20 %: STOT SE 3,	
Humber	^^^	H336;	

Millipore- 1.02644 Page 2 of 13



ethanol			
CAS-No.	64-17-5	Flam. Liq. 2; Eye Irrit. 2;	>= 10 - < 20
EC-No.	200-578-6	H225, H319	%
Index-No.	603-002-00-5	Concentration limits:	
Registration	01-2119457610-43-	>= 50 %: Eye Irrit. 2A,	
number	XXXX	H319;	

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Dry powder Foam

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

MERCK

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Protected from light.Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

MERCK

Component	CAS-No.	Value	Control parameters	Basis
Diethyl ether	60-29-7	TWA	100 ppm 308 mg/m3	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
	Remarks	Indicative		
		STEL	200 ppm 616 mg/m3	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
		Indicative		
		AGW	400 ppm 1.200 mg/m3	Germany. TRGS 900 - Occupational exposure limit values.
ethanol	64-17-5	AGW	200 ppm 380 mg/m3	Germany. TRGS 900 - Occupational exposure limit values.
		When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact Material: Viton®

Minimum layer thickness: 0,70 mm

Break through time: 30 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter AX (EN 371)

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Millipore- 1.02644 Page 5 of 13



Recommended Filter type: Filter type AX

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless

b) Odor ether-like

c) Odor Threshold No data available

d) pH at 20 °C

neutral

e) Melting No data available

point/freezing point

f) Initial boiling point ca.34 °C at 1.013 hPa and boiling range

g) Flash point -40 °C

h) Evaporation rate No data availablei) Flammability (solid, No data available

gas)

j) Upper/lower Upper explosion limit: 36 %(V) flammability or explosive limits Upper explosion limit: 1,7 %(V)

k) Vapor pressure 576 hPa at 20 °C
 l) Vapor density No data available
 m) Relative density No data available

n) Water solubility at 20 °C partly soluble, (as an emulsion)

o) Partition coefficient: No data available

n-octanol/water

p) Autoignition No data available temperature

q) Decomposition No data available temperature

r) Viscosity Viscosity, kinematic: No data available Viscosity, dynamic: No data available

Explosive properties No data available

Oxidizing properties No data available

9.2 Other safety information

No data available

Millipore- 1.02644 Page 6 of 13

SECTION 10: Stability and reactivity

10.1 Reactivity

Formation of peroxides possible.

Vapors may form explosive mixture with air.

10.2 Chemical stability

Sensitivity to light

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

chromyl chloride

Peroxides

Risk of explosion with:

azides

Halogens

halogen-halogen compounds

nonmetallic oxyhalides

Strong oxidizing agents

chromium(VI) oxide

halogen oxides

peroxi compounds

perchloric acid

perchlorates

Nitric acid

nitrating acid

Oxygen

Ozone

turpentine oils and/or turpentine substitutes

nitrates

metallic chlorides

salts of oxyhalogenic acids

nitrogen oxides

nonmetallic oxides

chromosulfuric acid

chlorates

hydrogen peroxide

permanganic acid

sulfuric acid

with

Nitric acid

sulfur

Risk of explosion during distillation.

Exothermic reaction with:

acid halides

10.4 Conditions to avoid

Moisture.

Warming.

Moisture.

10.5 Incompatible materials

Rubber, various plastics

10.6 Hazardous decomposition products

In the event of fire: see section 5

Millipore- 1.02644 Page 7 of 13

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Acute toxicity estimate Oral - 1.442 mg/kg

(Calculation method)

Inhalation: No data available Dermal: No data available

Skin corrosion/irritation

Repeated exposure with the mixture may cause skin dryness or cracking.

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Mixture may cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Components

Diethyl ether

Acute toxicity

LD50 Oral - Rat - 1.211 mg/kg

Remarks: (RTECS)

Symptoms: Risk of aspiration upon vomiting., Aspiration may cause pulmonary

edema and pneumonitis.

LC50 Inhalation - Mouse - 4 h - 97,5 mg/l

Remarks: (RTECS)

Symptoms: mucosal irritations

LD50 Dermal - Rabbit - male - > 20.000 mg/kg

(OECD Test Guideline 402)

Remarks: (ECHA)

Millipore- 1.02644 Page 8 of 13

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h (OECD Test Guideline 404)

Dermatitis

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation (OECD Test Guideline 405)

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Micronucleus test Test system: Human lymphocytes

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Mouse lymphoma test

Result: negative

Method: OECD Test Guideline 474 Species: Mouse - male and female

Result: negative **Carcinogenicity**

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness. - Central nervous system Acute oral toxicity - Risk of aspiration upon vomiting., Aspiration may cause pulmonary edema and pneumonitis.

Acute inhalation toxicity - mucosal irritations

Specific target organ toxicity - repeated exposure

Aspiration hazard

No data available

ethanol

Acute toxicity

LD50 Oral - Rat - male and female - 10.470 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Rat - male and female - 4 h - 124,7 mg/l

(OECD Test Guideline 403) Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 24 h

(OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes serious eye irritation.

(OECD Test Guideline 405)

Respiratory or skin sensitization

Maximization Test - Guinea pig

Result: negative

(OECD Test Guideline 406)

Remarks: (in analogy to similar products)

The value is given in analogy to the following substances: Methanol

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Result: negative

Method: OECD Test Guideline 478

Species: Mouse - male

Result: Positive results were obtained in some in vivo tests.

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Aspiration hazard

No data available

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Discharge into the environment must be avoided.

Millipore- 1.02644 Page 10 of 13

Components

Diethyl ether

Toxicity to fish LC50 - Leuciscus idus (Golden orfe) - 2.840 mg/l - 48 h

Remarks: (ECOTOX Database)

Toxicity to daphnia

and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 1.380 mg/l - 48 h

Remarks: (IUCLID)

Toxicity to algae static test ErC50 - Desmodesmus subspicatus (green algae) - >

100 mg/l - 72 h

(OECD Test Guideline 201)

Toxicity to bacteria static test EC50 - activated sludge - 21.000 mg/l - 3 h

(OECD Test Guideline 209)

static test NOEC - activated sludge - 42 mg/l - 3 h

(OECD Test Guideline 209)

ethanol

Toxicity to fish flow-through test LC50 - Pimephales promelas (fathead

minnow) - 15.300 mg/l - 96 h

(US-EPA)

Toxicity to daphnia

and other aquatic invertebrates

static test LC50 - Ceriodaphnia dubia (water flea) - 5.012 mg/l

- 48 h

nvertebrates Remarks: (ECHA)

Toxicity to algae static test ErC50 - Chlorella vulgaris (Fresh water algae) - 275

mg/l - 72 h

(OECD Test Guideline 201)

Toxicity to bacteria static test IC50 - activated sludge - > 1.000 mg/l - 3 h

(OECD Test Guideline 209)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions. Notice Directive on waste 2008/98/EC.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 2059 IMDG: 2059 IATA: 2059

14.2 UN proper shipping name

ADR/RID: NITROCELLULOSE SOLUTION, FLAMMABLE IMDG: NITROCELLULOSE SOLUTION, FLAMMABLE

IATA: Nitrocellulose solution, flammable

Millipore- 1.02644 Page 11 of 13



14.3 Transport hazard class(es)

ADR/RID: 3 IMDG: 3 IATA: 3

14.4 Packaging group

ADR/RID: I IMDG: I IATA: I

14.5 Environmental hazards

ADR/RID: no IMDG Marine pollutant: no IATA: no

14.6 Special precautions for user

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

National legislation

Seveso III: Directive 2012/18/EU of the European : FLAMMABLE LIQUIDS Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Water contaminating class (Germany):

WGK 3, highly water endangering Classification according to AwSV, Annex 1 (5.2)

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable.

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3.

EUH019	May form explosive peroxides.
EUH066	Repeated exposure may cause skin dryness or cracking.
H224	Extremely flammable liquid and vapor.
H225	Highly flammable liquid and vapor.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See

Millipore- 1.02644 Page 12 of 13



www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Millipore- 1.02644 Page 13 of 13

