

SAFETY DATA SHEET

Version 6.2 Revision Date 01.06.2021 Print Date 29.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name	: 1-Chlorobutane		
Product Number Brand	: 34958 : SIGALD		
Dianu	. SIGALD		
Index-No.	: 602-059-00-3		
CAS-No.	: 109-69-3		

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company	:	MilliporeSigma Canada Ltd 2149 WINSTON PARK DRIVE OAKVILLE ON L6H 6J8 CANADA
Telephone Fax		+1 905 829-9500 +1 905 829-9292
Emergency telephone		
Emergency Phone #	:	800-424-9300 CHEMTREC (USA) +1-703-527-3887 CHEMTREC

(International)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with Hazardous Products Regulations (HPR) (SOR/2015-17)

24 Hours/day; 7 Days/week

Flammable liquids (Category 2), H225 Aspiration hazard (Category 1), H304 Short-term (acute) aquatic hazard (Category 3), H402 Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



SIGALD - 34958

1.4

Page 1 of 10



Signal word	Danger
Hazard statement(s) H225 H304 H412	Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.
Precautionary statement(s)	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P331	Do NOT induce vomiting.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

- none

SECTION 3: Composition/information on ingredients

3.1 Substances

: Butyl chloride		
: C ₄ H ₉ Cl		
_ .		
: 203-696-6 : 602-059-00-3		
	Classification	Concentration *
	Flam. Liq. 2; Asp. Tox. 1; Aquatic Acute 3; Aquatic Chronic 3; H225, H304, H402, H412	<= 100 %
	: C ₄ H ₉ Cl : 92.57 g/mol : 109-69-3 : 203-696-6	: C ₄ H ₉ Cl : 92.57 g/mol : 109-69-3 : 203-696-6 : 602-059-00-3 Classification Flam. Liq. 2; Asp. Tox. 1; Aquatic Acute 3; Aquatic Chronic 3; H225, H304,

* Weight %

For the full text of the H-Statements mentioned in this Section, see Section 16. SIGALD - 34958

Page 2 of 10



SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

- **4.2 Most important symptoms and effects, both acute and delayed** The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
- **4.3 Indication of any immediate medical attention and special treatment needed** No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2) Foam Dry powder

Unsuitable extinguishing media For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides Hydrogen chloride gas Combustible. Pay attention to flashback. Vapors are heavier than air and may spread along floors. Development of hazardous combustion gases or vapours possible in the event of fire. Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

5.4 Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SIGALD - 34958

Page 3 of 10



SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.
- **6.2 Environmental precautions** Do not let product enter drains. Risk of explosion.
- 6.3 Methods and materials for containment and cleaning up Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.
- **6.4** Reference to other sections For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Change contaminated clothing. Wash hands after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

8.2 Exposure controls

Appropriate engineering controls

Change contaminated clothing. Wash hands after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

SIGALD - 34958

Page 4 of 10



Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Full contact Material: Viton®

Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Splash contact Material: butyl-rubber Minimum layer thickness: 0.7 mm Break through time: 10 min

Material tested:Butoject® (KCL 898)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a)	Appearance	Form: clear Color: colorless
b)	Odor	stinging
c)	Odor Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	Melting point/range: -123 °C (-189 °F) - lit.
f)	Initial boiling point and boiling range	77 - 78 °C 171 - 172 °F - lit.
g)	Flash point	-12 °C (10 °F) at ca.1,013.25 hPa - closed cup - Regulation (EC) No. 440/2008, Annex, A.9
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available

SIGALD - 34958

Page 5 of 10



j)	Upper/lower flammability or explosive limits	Upper explosion limit: 10.1 %(V) Lower explosion limit: 1.8 %(V)	
k)	Vapor pressure	120.6 hPa at 20 °C (68 °F) - OECD Test Guideline 104	
I)	Vapor density	3.2 - (Air = 1.0)	
m)	Relative density	0.88 at 20 °C (68 °F)	
n)	Water solubility	ca.0.11 g/l at 20 °C (68 °F) - OECD Test Guideline 105 - partly soluble	
o)	Partition coefficient: n-octanol/water	log Pow: 2.66 at 20 °C (68 °F) - OECD Test Guideline 107 - Bioaccumulation is not expected.	
p)	Autoignition temperature	245 °C (473 °F) at 1,013.25 hPa	
q)	Decomposition temperature	No data available	
r)	Viscosity	No data available	
s)	Explosive properties	No data available	
t)	Oxidizing properties	No data available	
Otł	Other safety information		

Surface tension63.2 mN/m at 0.1g/l at 20 °C (68 °F) - OECD Test Guideline 115Relative vapor
density3.2 - (Air = 1.0)

SECTION 10: Stability and reactivity

10.1 Reactivity

9.2

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Risk of explosion with: Alkali metals Alkaline earth metals sodium amide Risk of ignition or formation of inflammable gases or vapours with: Oxidizing agents Powdered light metals

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

various plastics, Light metals

10.6 Hazardous decomposition products In the event of fire: see section 5

SIGALD - 34958

Page 6 of 10



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 2,200 mg/kg Remarks: (RTECS) LC50 Inhalation - Rat - male and female - 4 h - > 7.74 mg/l (OECD Test Guideline 403) Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit Result: No skin irritation - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit Result: No eye irritation (OECD Test Guideline 405)

Respiratory or skin sensitization

Buehler Test - Guinea pig Result: negative (OECD Test Guideline 406)

Germ cell mutagenicity

Test Type: Ames test Test system: Salmonella typhimurium Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 471 Result: negative Test Type: Chromosome aberration test in vitro Test system: Chinese hamster cells Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 473 Result: negative Test Type: In vitro mammalian cell gene mutation test Test system: mouse lymphoma cells Metabolic activation: with and without metabolic activation Method: OECD Test Guideline 476 Result: negative

Test Type: Micronucleus test Species: Mouse Cell type: Bone marrow Application Route: Intraperitoneal Method: OECD Test Guideline 474 Result: negative

Carcinogenicity Animal testing did not show any carcinogenic effects.

Reproductive toxicity

No toxicity to reproduction No data available

Specific target organ toxicity - single exposure

SIGALD - 34958

Page 7 of 10



No data available

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 90 Days - NOAEL (No observed adverse effect level) - 120 mg/kg - LOAEL (Lowest observed adverse effect level) - 250 mg/kg

RTECS: EJ6300000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	semi-static test LC50 - Brachydanio rerio (zebrafish) - ca. 75.6 mg/l - 96 h (OECD Test Guideline 203)		
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - 452 mg/l - 48 h (Regulation (EC) No. 440/2008, Annex, C.2)		
Toxicity to algae	static test ErC50 - Desmodesmus subspicatus (green algae) - > 450 mg/l - 72 h (Regulation (EC) No. 440/2008, Annex, C.3)		
Toxicity to bacteria	static test EC50 - activated sludge - > 1,000 mg/l - 3 h (OECD Test Guideline 209)		
Dersistence and der	Porsistance and degradability		

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d Result: 47.2 % - Not readily biodegradable. (ISO 10708)

12.3 Bioaccumulative potential

Bioaccumulation Cyprinus carpio (Carp) - 6 Weeks at 25 °C - 0.5 mg/l(1-chlorobutane)

> Bioconcentration factor (BCF): 7.6 - 21 (OECD Test Guideline 305C)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

No data available

SIGALD - 34958

Page 8 of 10



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

TDG UN number: 1127 Class: 3 Proper shipping name: CHLOROBUTANES Labels: 3 ERG Code: 130 Marine pollutant: no	Packing group: II	
IMDG UN number: 1127 Class: 3 Proper shipping name: CHLOROBUTANES	Packing group: II	EMS-No: F-E, S-D
IATA UN number: 1127 Class: 3 Proper shipping name: Chlorobutanes	Packing group: II	

SECTION 15: Regulatory information

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

SECTION 16: Other information

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the

SIGALD - 34958

Page 9 of 10



information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 6.2 Revision Date: 01.06.2021 Print Date: 29.01.2022

SIGALD - 34958

Page 10 of 10

