

## SAFETY DATA SHEET

Version 8.6  
Revision Date 26.08.2021  
Print Date 15.02.2023

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Isohexane for analysis EMSURE®  
Product Number : 1.04333  
Catalogue No. : 104333  
Brand : Millipore  
Index-No. : 601-007-00-7

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Reagent for analysis, Chemical production

**1.3 Details of the supplier of the safety data sheet**

Company : SIGMA-ALDRICH CANADA LTD.  
2149 WINSTON PARK DRIVE  
OAKVILLE ON L6H 6J8  
CANADA  
Telephone : +1 905 829-9500  
Fax : +1 905 829-9292

**1.4 Emergency telephone**

Emergency Phone # : 800-424-9300 CHEMTREC (USA)  
+1-703-527-3887 CHEMTREC  
(International)  
24 Hours/day; 7 Days/week

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****GHS Classification in accordance with Hazardous Products Regulations (HPR) (SOR/2015-17)**

Flammable liquids (Category 2), H225  
Skin irritation (Category 2), H315  
Reproductive toxicity (Category 2), H361  
Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336  
Aspiration hazard (Category 1), H304  
Long-term (chronic) aquatic hazard (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

**2.2 GHS Label elements, including precautionary statements**

Pictogram



Signal word	Danger
Hazard statement(s)	
H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H411	Toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

- none

---

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Formula : C<sub>6</sub>H<sub>14</sub>  
 EC-No. : 295- 570-2

Millipore - 1.04333

Page 2 of 10

Index-No. : 601-007-00-7

Component	Classification	Concentration *
<b>Hydrocarbons, C6, isoalkanes,</b>		
	Flam. Liq. 2; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1; Aquatic Chronic 2; H225, H315, H336, H304, H411	<= 100 %
* Weight %		

<b>n-Hexane</b>		
	Flam. Liq. 2; Skin Irrit. 2; Repr. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1; Aquatic Acute 2; Aquatic Chronic 2; H225, H315, H361, H336, H373, H304, H401, H411 Concentration limits: >= 5 %: STOT RE 2, H373; >= 20 %: STOT SE 3, H336;	>= 1 - < 5 %
* Weight %		

For the full text of the H-Statements mentioned in this Section, see Section 16.

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

#### General advice

Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Call in physician.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

#### If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Foam Carbon dioxide (CO<sub>2</sub>) Dry powder

#### Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

### 5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Risk of dust explosion.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

### 5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

### 5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

### 6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

### 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

### 6.4 Reference to other sections

For disposal see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

#### Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

**Hygiene measures**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

**Storage class**

Storage class (TRGS 510): 3: Flammable liquids

**7.3 Specific end use(s)**

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

---

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Components with workplace control parameters**

Components	CAS-No.	Value	Control parameters	Basis
n-Hexane	110-54-3	TWA	50 ppm 176 mg/m3	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
Remarks	Substance may be readily absorbed through intact skin			
		TWA	20 ppm	Canada. British Columbia OEL
	Contributes significantly to the overall exposure by the skin route.			
		TWAEV	50 ppm 176 mg/m3	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
	Skin (percutaneous)			
		TWA	50 ppm	USA. ACGIH Threshold Limit Values (TLV)

**8.2 Exposure controls**

**Appropriate engineering controls**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

## Personal protective equipment

### Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.40 mm

Break through time: > 480 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: > 30 min

Material tested: Butoject® (KCL 898)

### Body Protection

Flame retardant antistatic protective clothing.

### Respiratory protection

required when vapours/aerosols are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

### Control of environmental exposure

Do not let product enter drains. Risk of explosion.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- |  |                                      |
|--|--------------------------------------|
| a) Appearance                              | Form: liquid<br>Color: colorless     |
| b) Odor                                    | benzine-like                         |
| c) Odor Threshold                          | No data available                    |
| d) pH                                      | No data available                    |
| e) Melting point/freezing point            | Melting point: < -50 °C (< -58 °F)   |
| f) Initial boiling point and boiling range | 53 - 63 °C 127 - 145 °F at 1,013 hPa |

g) Flash point	-21 °C (-6 °F) - c.c.
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 7.4 %(V) Lower explosion limit: 1.0 %(V)
k) Vapor pressure	160 - 190 hPa at 20 °C (68 °F)
l) Vapor density	No data available
m) Density	ca.0.66 g/cm <sup>3</sup> at 20 °C (68 °F)
Relative density	No data available
n) Water solubility	0.02 g/l at 20 °C (68 °F)
o) Partition coefficient: n-octanol/water	log Pow: 3.6 - 4 - (IUCLID), Bioaccumulation is not expected.
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	0.5 mm <sup>2</sup> /s at 20 °C (68 °F) -
s) Explosive properties	Not classified as explosive.
t) Oxidizing properties	none

## 9.2 Other safety information

No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Vapors may form explosive mixture with air.

### 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

### 10.3 Possibility of hazardous reactions

Risk of explosion with:

Risk of ignition or formation of inflammable gases or vapours with:

Oxidizing agents

### 10.4 Conditions to avoid

Warming.

### 10.5 Incompatible materials

Rubber, various plastics

### 10.6 Hazardous decomposition products

In the event of fire: see section 5

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - > 2,000 mg/kg

LD50 Oral - Rat - > 2,000 mg/kg (Hydrocarbons, C6, isoalkanes,)

Remarks: (External MSDS)

LC50 Inhalation - Rat - 4 h - > 5 mg/l (Hydrocarbons, C6, isoalkanes,)

Remarks: (External MSDS)

(Regulation (EC) No 1272/2008, Annex VI)

LD50 Dermal - Rabbit - > 2,000 mg/kg

LD50 Dermal - Rabbit - > 2,000 mg/kg (Hydrocarbons, C6, isoalkanes,)

Remarks: (External MSDS)

#### Skin corrosion/irritation

Causes skin irritation. Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2) (Hydrocarbons, C6, isoalkanes,)

#### Serious eye damage/eye irritation

No data available

#### Respiratory or skin sensitization

No data available

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

#### Reproductive toxicity

No data available

#### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness. - Central nervous system (Hydrocarbons, C6, isoalkanes,)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

#### Specific target organ toxicity - repeated exposure

No data available

#### Aspiration hazard

Aspiration hazard, Aspiration may cause pulmonary edema and pneumonitis. (Hydrocarbons, C6, isoalkanes,)

### 11.2 Additional Information

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. (Hydrocarbons, C6, isoalkanes,)

---

## SECTION 12: Ecological information

### 12.1 Toxicity

No data available

### 12.2 Persistence and degradability

Biodegradability

Remarks: (Lit.)

Millipore - 1.04333

Page 8 of 10



### 12.3 Bioaccumulative potential

No data available

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### 12.6 Other adverse effects

No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See [www.retrologistik.com](http://www.retrologistik.com) for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

---

## SECTION 14: Transport information

#### TDG

UN number: 1208 Class: 3 Packing group: II  
Proper shipping name: HEXANES  
Labels: 3  
ERG Code: 128  
Marine pollutant: no

#### IMDG

UN number: 1208 Class: 3 Packing group: II EMS-No: F-E, S-D  
Proper shipping name: HEXANES  
Marine pollutant : yes  
Marine pollutant : yes

#### IATA

UN number: 1208 Class: 3 Packing group: II  
Proper shipping name: Hexanes

---

## SECTION 15: Regulatory information

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

---

## SECTION 16: Other information

### Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact [mlsbranding@sial.com](mailto:mlsbranding@sial.com).

Version: 8.6

Revision Date: 26.08.2021

Print Date: 15.02.2023