

SAFETY DATA SHEET

Version 8.3
Revision Date 01.07.2021
Print Date 15.04.2023**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Benzaldehyde for synthesis

Product Number : 8.01756
Catalogue No. : 801756
Brand : Millipore
Index-No. : 605-012-00-5
CAS-No. : 100-52-7

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Chemical for synthesis

1.3 Details of the supplier of the safety data sheet

Company : SIGMA-ALDRICH CANADA LTD.
2149 WINSTON PARK DRIVE
OAKVILLE ON L6H 6J8
CANADA

Telephone : +1 905 829-9500
Fax : +1 905 829-9292

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA)
+1-703-527-3887 CHEMTREC
(International)
24 Hours/day; 7 Days/week

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****GHS Classification in accordance with Hazardous Products Regulations (HPR) (SOR/2015-17)**

Flammable liquids (Category 4), H227
Acute toxicity, Oral (Category 4), H302
Acute toxicity, Inhalation (Category 4), H332
Skin irritation (Category 2), H315
Eye irritation (Category 2A), H319
Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335
Short-term (acute) aquatic hazard (Category 2), H401
Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Warning

Hazard statement(s)

H227	Combustible liquid.
H302 + H332	Harmful if swallowed or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H401	Toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statement(s)

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P302 + P352	IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

- none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula	: C7H6O
Molecular weight	: 106.12 g/mol
CAS-No.	: 100-52-7
EC-No.	: 202-860-4
Index-No.	: 605-012-00-5

Millipore - 8.01756

Page 2 of 10

Component	Classification	Concentration *
benzaldehyde		
	Flam. Liq. 4; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2A; STOT SE 3; Aquatic Acute 2; Aquatic Chronic 3; H227, H302, H332, H315, H319, H335, H401, H412	<= 100 %
* Weight %		

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides
Combustible.

Vapors are heavier than air and may spread along floors.
Forms explosive mixtures with air on intense heating.
Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Protected from light. Tightly closed.

Recommended storage temperature see product label.

Storage class (TRGS 510): 10: Combustible liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Basis
benzaldehyde	100-52-7	STEL	4 ppm 17 mg/m ³	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Latex gloves

Minimum layer thickness: 0.6 mm

Break through time: 10 min

Material tested: Lapren® (KCL 706 / Aldrich Z677558, Size M)

Body Protection

protective clothing

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance	Form: liquid Color: colorless, to, light yellow
b) Odor	No data available
c) Odor Threshold	No data available
d) pH	5.9 at 20 °C (68 °F)
e) Melting point/freezing point	Melting point/freezing point: -26 °C (-15 °F)
f) Initial boiling point and boiling range	177 - 179 °C 351 - 354 °F at 1,013 hPa
g) Flash point	63 °C (145 °F) - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	No data available
j) Upper/lower flammability or explosive limits	Upper explosion limit: 8.5 %(V) Lower explosion limit: 1.4 %(V)
k) Vapor pressure	1.69 hPa at 25 °C (77 °F)
l) Vapor density	3.66 - (Air = 1.0)
m) Relative density	No data available
n) Water solubility	6.95 g/l at 25 °C (77 °F)
o) Partition coefficient: n-octanol/water	log Pow: 1.4 at 25 °C (77 °F) - Bioaccumulation is not expected.
p) Autoignition temperature	No data available
q) Decomposition temperature	No data available
r) Viscosity	No data available
s) Explosive properties	No data available
t) Oxidizing properties	No data available

9.2 Other safety information

Surface tension	70.5 mN/m at 1g/l at 20 °C (68 °F) - OECD Test Guideline 115
Relative vapor density	3.66 - (Air = 1.0)

SECTION 10: Stability and reactivity

10.1 Reactivity

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Violent reactions possible with:

bases
Alkali metals
Aluminum
Iron
performic acid
phenols
Oxygen
Oxidizing agents

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

Aluminum, various plastics, Strong oxidizing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male - 1,430 mg/kg
(OECD Test Guideline 401)
LC50 Inhalation - Rat - male and female - 4 h - 1 - 5 mg/l
(OECD Test Guideline 436)
LD50 Dermal - Rabbit - > 1,250 mg/kg
Remarks: (RTECS)
No data available

Skin corrosion/irritation

Skin - Rabbit
Result: Moderate skin irritation - 24 h
(Draize Test)

Serious eye damage/eye irritation

Eyes - Rabbit
Result: slight irritation
(OECD Test Guideline 405)

Respiratory or skin sensitization

Maximization Test - Guinea pig
Result: Does not cause skin sensitization.
(OECD Test Guideline 406)
- Guinea pig
Result: Does not cause respiratory sensitization.
Remarks: (ECHA)

Germ cell mutagenicity

Test Type: In vitro mammalian cell gene mutation test
Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 490

Result: negative

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation. - Lungs

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Central nervous system depression, Prolonged or repeated exposure to skin causes defatting and dermatitis., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption:

Damage to:

Kidney

Systemic effects:

Headache

Drowsiness

Convulsions

Dizziness

Shortness of breath

Unconsciousness

narcosis

Other dangerous properties can not be excluded.

Handle in accordance with good industrial hygiene and safety practice.

Liver - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish flow-through test LC50 - *Lepomis macrochirus* - 1.07 mg/l - 96 h
(OECD Test Guideline 203)

Toxicity to daphnia semi-static test EC50 - *Daphnia magna* (Water flea) - 19.7 mg/l - 48
and other aquatic h
invertebrates (OECD Test Guideline 202)

Millipore - 8.01756

Page 8 of 10

Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata - 33.1 mg/l - 72 h
(OECD Test Guideline 201)

Toxicity to bacteria static test IC50 - activated sludge - 759.3 mg/l - 3 h
(OECD Test Guideline 209)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d
Result: 95 % - Readily biodegradable.
(OECD Test Guideline 301B)

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

Forms toxic mixtures in water, dilution measures notwithstanding.
Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information

TDG

UN number: 1990 Class: 9 Packing group: III
Proper shipping name: BENZALDEHYDE
Labels: 9
ERG Code: 129
Marine pollutant: no

IMDG

UN number: 1990 Class: 9 Packing group: III EMS-No: F-A, S-A
Proper shipping name: BENZALDEHYDE

IATA

UN number: 1990 Class: 9 Packing group: III
Proper shipping name: Benzaldehyde

SECTION 15: Regulatory information

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR.

SECTION 16: Other information**Further information**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.3

Revision Date: 01.07.2021

Print Date: 15.04.2023